## **Forklift Training Course Ottawa**

Forklift Training Course Ottawa - OSHA and CSA establish criteria for forklift safety training that meets current standards and regulations. Anyone intending to operate a forklift is needed to successfully finish safety training prior to using whichever type of forklift. The accredited Forklift Operator Training Program is intended to offer people training with the information and practical skills to become an operator of a forklift.

There are forklift operation safety regulations which should be followed pertaining to pre-shift inspections, and regulations for loading and lifting.

Prior to a shift beginning, an inspection checklist should be carried out and submitted to the Supervisor or Instructor. If whatever maintenance issue is discovered, the equipment should not be operated until the problem is addressed. To indicate the machinery is out of service, the keys must be removed from the ignition and a warning tag placed in a place that is seen.

Safety rules for loading will consist of checking the forklift's load rating capacity to determine how much the equipment could handle. When starting the machinery, the forks should be in the downward position. Remember that there is a loss of approximately 100 pounds carrying capacity for every one inch further away from the carriage which the load is carried.

Lifting should start with the driver moving to a stopped position roughly three inches from the load. The mast must then be leveled until it has reached a right angle with the load. Lift the forks to an inch below the slot on the pallet and drive forward. After that lift forks four inches. Tilt back the load to secure it for moving. Drive the lift in reverse if the load obscures frontal vision. Check behind and honk to alert other personnel. Never allow forks to drag on the ground.

Forklift loads must be loaded in such a way that they are secure and do not create a danger to other objects or people. Restraining loads is necessary for materials which may shift during transport and destabilize the forklift.

To be able to avoid the movement of drums, drums could be strapped together to reduce movement. Operators of forklifts should drive slowly when moving liquids, to reduce instability in the forklift.